

BOUJINTEX #8700DL BASE

SAFETY DATA SHEET

<1. Product and company identification >

Product Name BOUJINTEX #8700DL BASE
Reference No. 5802-0000
Company MIZUTANI PAINT CO., LTD.
Address 03-90,NISHIMIKUNI 4-CHOME YODOGAWA-KU,OSAKA,JAPAN
Section concerned Quality Assurance Dep.
Phone No. 06-6394-2653 FAX No. 06-6391-3429
Emergency contact Mizutani Paint Co., Ltd. Production Dep.
Emergency phone No. 06-6391-3151
Product type Solvent based epoxy resin paint BASE
Principal use Building materials use, others
Date Feb.10,1994
Revision day Dec.22,2016

<2. Hazards identification >

[GHS classification]

Flammable liquids : Not classified
Acute toxicity (oral) : Not classified
Acute toxicity (skin) : Not classified
Acute toxicity (inhalation: gas) : Not classified
Acute toxicity (inhalation: vapour) : Category 4
Acute toxicity (inhalation: dust, mist) : Not classified
Skin corrosion / irritation : Category 2
Serious eye damages / eye irritation : Category 2
Respiratory sensitization : Classification not possible
Skin sensitization : Category 1
Germ cell mutagenicity : Not classified
Carcinogenicity : Category 2
Reproductive toxicity : Not classified
Specific target organ toxicity single exposure : Not classified
Specific target organ toxicity repeated exposure : Not classified
Aspiration hazard : Not applicable
Aquatic toxicity (acute) : Category 1
Aquatic toxicity (chronic) : Category 1
Hazardous to the ozone layer : Classification not possible
[GHS label elements including precautionary statements]



Signal word : DANGER

[Hazard statement]

- Causes skin irritation.
- Causes serious eye irritation.
- May causes an allergic skin reaction.
- Suspected of causing cancer.
- Causes damage to organs through prolonged or repeated exposure.
- Very toxic to aquatic life.
- Very toxic to aquatic life with long lasting effects.

BOUJINTEX #8700DL BASE

[Precautionary statements]

【Prevention】

- Keep container tightly closed.
- Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
- Use explosion-proof electrical/ventilating/lighting/ equipment.
- Do not eat, drink or smoke when using this product.
- Wear protective gloves/protective clothing/eye protection/face protection.
- Use only outdoors or in well-ventilated area.
- Wash hands thoroughly after handling.
- Avoid release to the environment.

【Response】

- In case of fire: Don't use water. Use the specific extinguishing media (Powder, CO₂, Foams).
- If in eyes: Rinse cautiously with water for 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a physician.
- If swallowed: Rinse mouth with water. Do not induce vomiting. Immediately call a physician.
- If on skin : Remove all contaminated clothing. Wash with plenty of soap and water.
- Arrange medical treatment by a physician on injured skin and painful parts.
- If inhaled: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
- If exposed or concerned, or if you feel unwell: Get medical advice/attention.
- At the leakage: Collect spillage.

【Storage】

- Store in a dry place. Keep container tightly closed in the locked place.

【Disposal】

- Dispose of contents / container to waste in accordance with local / regional / national / International regulations (to be specified).

<3. Composition/information on ingredients >

Distinction of chemical or mixture: mixture

Hazardous, harmful element:

Chemistry substance name	Cas No.	Content(%)	Note
Diglycidylether of BPA	25068-38-6	40 ~ 50	
Silica	7631-86-9	~ 1	
Titanium dioxide	13463-67-7	~ 10	
Synthetic iron oxide yellow	51274-00-1	~ 5	
Ferric oxide	1309-37-1	~ 5	
Phthalocyanine blue	147-14-8	~ 5	
Phthalocyanine green	1328-53-6	~ 5	
Carbon black	1333-86-4	~ 5	

<4. First-aid measures >

Eye contact :

- Wash 15 minutes or more with plenty of clean water immediately. Wash completely to the reverse side of an eyelid.
- Receive the diagnosis of physician as soon as possible.

Skin contact :

- Wipe quickly clinging matter with clean cloth.
- Wash the affected area with plenty of running water using a mild soap or skin shampoo. Don't use solvents and thinner.
- Arrange medical treatment by a physician on injured skin and painful parts.

BOUJINTEX #8700DL BASE

Inhalation :

- Remove the victim inhale solvent vapor and gasses in abundance to fresh air and keep in warm and quiet. If breathing is weak, irregular or has stopped, open his airway, loose his collar and belt and administer artificial respiration. Arrange medical treatment by a physician as soon as possible.
- Remove the victim inhale vapor and gasses of organic solvents and more to fresh air and keep quiet. Then, arrange medical care.

Ingestion :

- If swallow in the wrong, keep the victim quiet and arrange medical inspection by physician, immediately.
- Prevent to swallow the vomiting.
- Don't vomit things forcibly except dependence on the instruction of physician.

<5. Fire-fighting measures >

Extinction medicine : Powder, CO₂, Foams

Specific extinction method :

- Don't use water. • Use the specific extinguishing media.
- Fire-fighters should wear proper protective equipment's (Fire-proof wares etc.,)
- Remove Flammable materials near fire immediately.
- Cool the airtight container exposed to the high temperature sprinkling water.
- Do the extinction activity from the windward.

<6. Accidental release measures >

- Wear proper protective equipment's (Gloves, protective mask, apron and goggles)
- Take up and place in closed container and keep in safety zone.
- Ensure treatment of the contaminated and waste in compliance with government requirements.
- Absorb spill with inner materials (e.g. dry sand, earth) then place in a chemical waste containers. For large spills, dike for pollution further release.
- Shut off all source of ignition, heat, and Flammable materials immediately.
- Prepare proper fire-extinguisher for the fire.
- Take up the spill by equipment made of plastics to avoid sparks.
- Be careful not to be exhausted to the river etc. and be careful not to cause the influence on the environment.

<7. Handling and storage >

Handling :

- Use only in the well-ventilated areas. • Keep container tightly and closely.
- Keep away from fire, spark and heat in using area.
- Equipment should be grounded and bonded. Use explosion proof electrical equipment.
- Use reduced-sparking hand-tools.
- Use the uniform and the work shoes of the electrification prevention type while working.
- Use adequate exhaust ventilation in closed area and ware proper protective equipment during using these materials.
- Wear a protection tool appropriate which touches eyes, the skins, mucous membranes, and clothes.
- Wash your the hand and face, etc. well after handling. Don't bring the pollution protection tool into the rest room.
- The person who has experienced an allergic condition in the past must not handle this product.

Storage :

- Protect from direct sunlight.
- Store in a cool dry, well-ventilated location.
- Keep away from fire and heat.

BOUJINTEX #8700DL BASE

<8. Exposure controls/protection >

Exposure density of hazardous, harmful element :

Chemistry substance name	Management density	ACGIH (TLV)
Titanium dioxide	—	10 mg/m ³

Equipment requirement :

- Use non-spark closed type equipment.
- Prevent remaining vapors with adequate ventilation.
- Equipment should be grounded and bonded in case of transport, suction and stirring liquids.
- Don't use equipment having high temperature and source of fire around handling this materials.
- In poor ventilated area, use automatic spraying equipment and adequate ventilator to avoid direct workers' exposure to solvent vapors.
- In the closed area of tank, use ventilator effective to closed and bottom area.

Protection tool :

- Eye protection ; Wear protective goggles.
- Skin protection ; Wear impervious clothing such as gloves, apron and body suits.
- Respiratory protection ; Use a respiratory protection mask for organic solvent gasses.
Wear positive pressure self-contained breathing apparatus in closed area.
- Others ; Wear the energizing shoes when you paint static electricity.

<9. Physical and chemical properties >

Appearance :

- Form : Liquids
- Color : The color has been described to the product name.
- Odor : Solvent odor

Specific temperatures/temperature ranges at which changes in physical state occur :

- Flashpoint ; 123 °C
- Density ; 1.53 ~ 1.60 g/cm³
- Solubility ; It doesn't melt to water

<10. Stability and reactivity >

Stability:

- There is no problem in stability in preservation under the room temperature.

Hazardous polymerization reaction:

- The product unit is not polymerized. After BASE and HARDENER are mixed, if left to itself, the mixture gels.
- It reacts with amines, amides, and the acid, etc.

Conditions to avoid:

- Don't heat the product. Pressure rises abnormally in the airtight container, and there are an explosion and dread of the ignition.

Hazardous decomposition products;

- CO and a harmful gas such as NO_x might be generated by combustion etc.

<11. Toxicological information >

Acute toxicity (inhalation: vapour) : Category 4

Skin corrosion / irritation : Category 2

Serious eye damages / eye irritation : Category 2

Skin sensitization : Category 1

Carcinogenicity : Category 2

<12. Ecological information >

Aquatic toxicity (acute) : Category 1

Aquatic toxicity (chronic) : Category 1

- Note the handling of the leakage thing and waste because it might influence the environment.
- Deal so that neither the product nor the washing water may flow directly to ground, the river, and the drain ditch.
- Information is not possessed about decomposition, accumulation, and the fish toxicity of the product.

BOUJINTEX #8700DL BASE

<13. Disposal considerations >

- Waste paints and opened containers should be asked to dispose with licensed industrial waste treatment company.
- Don't wash away the water used for cleaning of vessels and equipment into shower or water way.
- The wastes producing from process of water refining and of incineration should be disposed of in accordance with governmental laws and environmental control regulations or asked to dispose with licensed special company.

<14. Transport information >

General :

- Transport and store according to general caution and instructions in before mentioned comment.
- Load the product for the fall and no damage after it is confirmed that there is no leakage in the container.
- Do the collapse of cargo piles prevention surely.

Land transportation:

- Transport this product in compliance with the Fire-fighting Law, Law of Industrial Safety & Hygiene and Poisonous & Deleterious Material Control Law, if any.

Maritime transportation

- Maritime transportation should be in compliance with 「SENPAKU-ANZEN-HOU」

Air transportation:

- Air transportation should be in compliance with the Aviation Act.

U.N. Number : Class 9 (Environmentally hazardous substance, liquid, n.o.s.),

UN3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. P.G.III

<15. Regulatory information >

Law of Industrial Safety and Hygiene.

Chemical Substances Control Law.

Fire-fighting Law : Class 4 , No.3 class petroleum.

<16. Other information >

The main quotation document :

- Japan Paint Manufacturers Association edit " The SDS label preparation guidebook corresponding to GHS"
- Japan Paint Manufacturers Association edit " The substance database for SDS"
- Solvent pocket book

The information and recommendations in this publication are to the best of our knowledge, information and belief accurate at the date of publication. Nothing herein in to be construed as a warranty, express or implied.

In all cases it is the responsibility of the users to determine the applicability of such information or the suitability of any products for their own particular purpose.

BOUJINTEX #8700DL BASE

Composition table for SAFETY DATA SHEET

Product Name	BOUJINTEX #8700DL BASE
--------------	------------------------

Color name	Chemistry substance							
	①	②	③	④	⑤	⑥	⑦	⑧
WHITE	45.0	0.1~1	5~10	—	—	—	—	—
OCHRE	45.0	—	—	1~ 5	—	—	—	—
RUST	45.0	—	—	—	1~ 5	—	—	—
KON Y	45.0	—	—	—	—	1~ 5	—	—
KON R	45.0	—	—	—	—	1~ 5	—	—
GREEN	45.0	—	—	—	—	—	1~ 5	—
BLACK	45.0	—	—	—	—	—	—	1~ 5
YELLOW	45.0	—	—	—	—	—	—	—
RED	45.0	—	—	—	—	—	—	—
No.1 ORANGE BROWN	45.0	0.1~1	1~ 5	1~ 5	—	—	—	—
No.9 LIGHT GREEN	45.0	0.1~1	1~ 5	1~ 5	—	0.1~1	—	—
No.10 GREEN	45.0	—	1~ 5	—	—	0.1~1	—	0.1~1
No.16 LIGHT BEIGE	45.0	0.1~1	5~10	—	—	—	—	—
No.17 BEIGE	45.0	0.1~1	5~10	—	—	—	—	—
No.19 LIGHT GRAY	45.0	0.1~1	5~10	—	—	—	—	—
No.21 FRESH GREEN	45.0	0.1~1	1~ 5	—	—	0.1~1	—	—
No.22 HARMONY GREEN	45.0	0.1~1	1~ 5	—	—	—	—	—
No.23 OLIVE	45.0	0.1~1	1~ 5	1~ 5	—	—	—	—
No.24 AQUA GRAY	45.0	0.1~1	5~10	—	—	—	—	—
No.25 BLUE GRAY	45.0	0.1~1	1~ 5	—	—	0.1~1	—	—
No.26 SAND BEIGE	45.0	0.1~1	1~ 5	—	—	—	—	—
No.27 MOCHA BROWN	45.0	0.1~1	1~ 5	1~ 5	—	—	—	—
No.28 GOLD BROWN	45.0	—	1~ 5	—	1~ 5	—	—	—
No.29 NEW BROWN	45.0	0.1~1	—	—	1~ 5	—	—	—
No.30 FEVER GREEN	45.0	0.1~1	1~ 5	—	—	—	0.1~1	—
No.32 GRAY	45.0	0.1~1	1~ 5	—	—	—	—	0.1~1

Chemistry substance name :

- ① Diglycidylether of BPA
- ② Silica
- ③ Titanium dioxide
- ④ Synthetic iron oxide yellow
- ⑤ Ferric oxide
- ⑥ Phthalocyanine blue
- ⑦ Phthalocyanine green
- ⑧ Carbon black

BOUJINTEX #8700DL HARDENER S

SAFETY DATA SHEET

<1. Product and company identification >

Product Name BOUJINTEX #8700DL HARDENER S
Reference No. 5802-0188
Company MIZUTANI PAINT CO., LTD.
Address 03-90,NISHIMIKUNI 4-CHOME YODOGAWA-KU,OSAKA,JAPAN
Section concerned Quality Assurance Dep.
Phone No. 06-6394-2653 FAX No. 06-6391-3429
Emergency contact Mizutani Paint Co., Ltd. Production Dep.
Emergency phone No. 06-6391-3151
Product type Solvent based epoxy resin paint HARDENER
Principal use Building materials use, others
Date Feb.10,1994
Revision day Dec.22,2016

<2. Hazards identification >

[GHS classification]

Flammable liquids : Not classified
Acute toxicity (oral) : Not classified
Acute toxicity (skin) : Classification not possible
Acute toxicity (inhalation: gas) : Classification not possible
Acute toxicity (inhalation: vapour) : Not classified
Acute toxicity (inhalation: dust, mist) : Classification not possible
Skin corrosion / irritation : Category 2
Serious eye damages / eye irritation : Category 1
Respiratory sensitization : Classification not possible
Skin sensitization : Category 1
Germ cell mutagenicity : Not classified
Carcinogenicity : Classification not possible
Reproductive toxicity : Not classified
Specific target organ toxicity single exposure : Category 2 (Lung)
Specific target organ toxicity repeated exposure : Not classified
Aspiration hazard : Classification not possible
Aquatic toxicity (acute) : Not classified
Aquatic toxicity (chronic) : Not classified
Hazardous to the ozone layer : Classification not possible

[GHS label elements including precautionary statements]



Signal word : DANGER

[Hazard statement]

- Causes skin irritation.
- Causes serious eye damage.
- May causes an allergic skin reaction.
- Causes damage to organs.

[Precautionary statements]

【Prevention】

- Keep container tightly closed.

BOUJINTEX #8700DL HARDENER S

- Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
- Use explosion-proof electrical/ventilating/lighting/ equipment.
- Do not eat, drink or smoke when using this product.
- Wear protective gloves/protective clothing/eye protection/face protection.
- Use only outdoors or in well-ventilated area.
- Wash hands thoroughly after handling.
- Avoid release to the environment.

【Response】

- In case of fire: Don't use water. Use the specific extinguishing media (Powder, CO₂, Foams).
- If in eyes: Rinse cautiously with water for 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a physician.
- If swallowed: Rinse mouth with water. Do not induce vomiting. Immediately call a physician.
- If on skin : Remove all contaminated clothing. Wash with plenty of soap and water.
- Arrange medical treatment by a physician on injured skin and painful parts.
- If inhaled: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
- If exposed or concerned, or if you feel unwell: Get medical advice/attention.
- At the leakage: Collect spillage.

【Storage】

- Store in a dry place. Keep container tightly closed in the locked place.

【Disposal】

- Dispose of contents / container to waste in accordance with local / regional / national / international regulations (to be specified).

<3. Composition/information on ingredients >

Distinction of chemical or mixture : mixture

Hazardous, harmful element :

Chemistry substance name	CAS No.	Content(%)	Note
Modified polyamine	—	90 ~ 95	Confidential
M-Xylenediamine	1477-55-0	2 ~ 6	

<4. First-aid measures >

Eye contact :

- Wash 15 minutes or more with plenty of clean water immediately. Wash completely to the reverse side of an eyelid.
- Receive the diagnosis of physician as soon as possible.

Skin contact :

- Wipe quickly clinging matter with clean cloth.
- Wash the affected area with plenty of running water using a mild soap or skin shampoo. Don't use solvents and thinner.
- Arrange medical treatment by a physician on injured skin and painful parts.

Inhalation :

- Remove the victim inhale solvent vapor and gasses in abundance to fresh air and keep in warm and quiet. If breathing is weak, irregular or has stopped, open his airway, loose his collar and belt and administer artificial respiration. Arrange medical treatment by a physician as soon as possible.
- Remove the victim inhale vapor and gasses of organic solvents and more to fresh air and keep quiet. Then, arrange medical care.

Ingestion :

- If swallow in the wrong, keep the victim quiet and arrange medical inspection by physician, immediately.
- Prevent to swallow the vomiting.
- Don't vomit things forcibly except dependence on the instruction of physician.

BOUJINTEX #8700DL HARDENER S

<5. Fire-fighting measures >

Exinction medicine : Powder, CO₂, Foams

Specific extinction method :

- Don't use water. • Use the specific extinguishing media.
- Fire-fighters should wear proper protective equipment's (Fire-proof wares etc.,)
- Remove Flammable materials near fire immediately.
- Cool the airtight container exposed to the high temperature sprinkling water.
- Do the extinction activity from the windward.

<6. Accidental release measures >

- Wear proper protective equipment's (Gloves, protective mask, apron and goggles)
- Take up and place in closed container and keep in safety zone.
- Ensure treatment of the contaminated and waste in compliance with government requirements.
- Absorb spill with inner materials (e.g. dry sand, earth) then place in a chemical waste containers. For large spills, dike for pollution further release.
- Shut off all source of ignition, heat, and Flammable materials immediately.
- Prepare proper fire-extinguisher for the fire.
- Take up the spill by equipment made of plastics to avoid sparks.
- Be careful not to be exhausted to the river etc. and be careful not to cause the influence on the environment.

<7. Handling and storage >

Handling :

- Use only in the well-ventilated areas. • Keep container tightly and closely.
- Keep away from fire, spark and heat in using area.
- Equipment should be grounded and bonded. Use explosion proof electrical equipment.
- Use reduced-sparking hand-tools.
- Use the uniform and the work shoes of the electrification prevention type while working.
- Use adequate exhaust ventilation in closed area and ware proper protective equipment during using these materials.
- Wear a protection tool appropriate which touches eyes, the skins, mucous membranes, and clothes.
- Wash your the hand and face, etc. well after handling. Don't bring the pollution protection tool into the rest room.
- The person who has experienced an allergic condition in the past must not handle this product.

Storage :

- Protect from direct sunlight.
- Store in a cool dry, well-ventilated location.
- Keep away from fire and heat.

<8. Exposure controls/protection >

Equipment requirement :

- Use non-spark closed type equipment.
- Prevent remaining vapors with adequate ventilation.
- Equipment should be grounded and bonded in case of transport, suction and stirring liquids.
- Don't use equipment having high temperature and source of fire around handling this materials.
- In poor ventilated area, use automatic spraying equipment and adequate ventilator to avoid direct workers' exposure to solvent vapors.
- In the closed area of tank, use ventilator effective to closed and bottom area.

Protection tool :

- Eye protection ; Wear protective goggles.
- Skin protection ; Wear impervious clothing such as gloves, apron and body suits.
- Respiratory protection ; Use a respiratory protection mask for organic solvent gasses.
Wear positive pressure self-contained breathing apparatus in closed area.

BOUJINTEX #8700DL HARDENER S

- Others ; Wear the energizing shoes when you paint static electricity.

<9. Physical and chemical properties >

Appearance :

- Form : Liquids
- Color : Tan transparency
- Odor : Solvent odor

Specific temperatures/temperature ranges at which changes in physical state occur :

- Flashpoint ; 117 °C
- Density ; 1.02 ~ 1.08 g/cm³
- Solubility ; It doesn't melt to water

<10. Stability and reactivity >

Stability:

- There is no problem in stability in preservation under the room temperature.

Hazardous polymerization reaction:

- The product unit is not polymerized.

Conditions to avoid:

- Don't heat the product. Pressure rises abnormally in the airtight container, and there are an explosion and dread of the ignition.

Hazardous decomposition products;

- CO and a harmful gas such as NO_x might be generated by combustion etc.

<11. Toxicological information >

Skin corrosion / irritation : Category 2

Serious eye damages / eye irritation : Category 1

Skin sensitization : Category 1

Specific target organ toxicity single exposure : Category 2 (Lung)

<12. Ecological information >

- Note the handling of the leakage thing and waste because it might influence the environment.
- Deal so that neither the product nor the washing water may flow directly to ground, the river, and the drain ditch.
- Information is not possessed about decomposition, accumulation, and the fish toxicity of the product.

<13. Disposal considerations >

- Waste paints and opened containers should be asked to dispose with licensed industrial waste treatment company.
- Don't wash away the water used for cleaning of vessels and equipment into shower or water way.
- The wastes producing from process of water refining and of incineration should be disposed of in accordance with governmental laws and environmental control regulations or asked of dispose with licensed special company.

<14. Transport information >

General :

- Transport and store according to general caution and instructions in before mentioned comment.
- Load the product for the fall and no damage after it is confirmed that there is no leakage in the container.
- Do the collapse of cargo piles prevention surely.

Land transportation:

- Transport this product in compliance with the Fire-fighting Law, Law of Industrial Safety & Hygiene and Poisonous & Deleterious Material Control Law, if any.

Maritime transportation:

- Maritime transportation should be in compliance with 「SEMPAKU-ANZEN-HOU」

Air transportation:

- Air transportation should be in compliance with the Aviation Act.

U.N. Number : Class 8 (Corrosive), UN3267 CORROSIVE LIQUID BASIC, ORGANIC, N.O.S. P.G. III

BOUJINTEX #8700DL HARDENER S

<15. Regulatory information >

Law of Industrial Safety and Hygiene.

Fire-fighting Law : Class 4 , No.3 class petroleum.

<16. Other information >

The main quotation document :

- Japan Paint Manufacturers Association edit " The SDS label preparation guidebook corresponding to GHS"
- Japan Paint Manufacturers Association edit " The substance database for SDS"
- Solvent pocket book

The information and recommendations in this publication are to the best of our knowledge, information and belief accurate at the date of publication. Nothing herein in to be construed as a warranty, express or implied.

In all cases it is the responsibility of the users to determine the applicability of such information or the suitability of any products for their own particular purpose.