

4-3-90 Nishimikuni, Yodogawa-ku, Osaka Japan TEL 81-6-6391-3151 FAX 81-6-6393-1101 3536-0000-B 1/4

MIZUKEI BOUJINTEX PROEPO PRIMER BASE

SAFETY DATA SHEET

<1. Product and company identification > Product Name MIZUKEI BOUJINTEX PROEPO PRIMER BASE Reference No. 3536-0000 Company MIZUTANI PAINT CO., LTD. 03-90, NISHIMIKUNI 4-CHOME YODOGAWA-KU, OSAKA, JAPAN Address Section concerned Quality Assurance Dep. 06-6394-2653 FAX No. 06-6391-3429 Phone No. Emergency contact Mizutani Paint Co., Ltd. Production Dep. Emergency phone No. 06-6391-3151 Product type Water soluble epoxy resin paint, under coat BASE Principal use Building materials use, others Feb.15, 2016 Date Revision day Dec.12, 2018 <2. Hazards identification > [GHS classification] Flammable liquids : Not classified Acute toxicity (oral) : Not classified Acute toxicity (skin) : Not classified Acute toxicity (inhalation: gas) : Not applicable Acute toxicity (inhalation: vapour) : Not classified Acute toxicity (inhalation: dust, mist) : Not classified Skin corrosion / irritation : Not classified Serious eye damages / eye irritation : Not classified Respiratory sensitization : Classification not possible Skin sensitization : Classification not possible Germ cell mutagenicity : Not classified Carcinogenicity : Not classified Reproductive toxicity : Not classified Specific target organ toxicity single exposure : Not classified Specific target organ toxicity repeated exposure : Not classified Aspiration hazard : Not classified Aquatic toxicity (acute) : Not classified Aquatic toxicity (chronic) : Not classified Hazardous to the ozone layer : Classification not possible [GHS label elements including precautionary statements] [Hazard statement] [Precautionary statements] [Prevention] Keep container tightly closed. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not eat, drink or smoke when using this product. · Wear protective gloves/protective clothing/eye protection/face protection. · Use only outdoors or in well-ventilated area. · Wash hands thoroughly after handling. · Avoid release to the environment. to do. Continue rinsing. Immediately call a physician.

MIZUTANI PAINT CO., LTD. 4-3-90 Nishimikuni, Yodogawa-ku, Osaka Japan TEL 81-6-6391-3151 FAX 81-6-6393-1101 3536-0000-B 2/4

MIZUKEI BOUJINTEX PROEPO PRIMER BASE

[Response]

- · If in eyes: Rinse cautiously with water for 15 minutes. Remove contact lenses, if present and easy
- · If swallowed: Rinse mouth with water. Do not induce vomiting. Immediately call a physician.
- · If on skin : Remove all contaminated clothing. Wash with plenty of soap and water.
- · Arrange medical treatment by a physician on injured skin and painful parts.
- · If inhaled: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
- · If exposed or concerned, or if you feel unwell: Get medical advice/attention.
- At the leakage: Collect spillage.

[Storage]

· Store in a dry place. Keep container tightly closed in the locked place.

[Disposal]

- Dispose of contents / container to waste in accordance with local / regional / national / international regulations (to be specified).
- <3. Composition/information on ingredients >
 - Distinction of chemical or mixture : mixture
 - Hazardous, harmful element :

Chemistry substance name	CAS No.	Content(%)	Note
Modified aliphatic polyamine	_	10 ~ 20	Confidential
2-(Dimethylamino)ethanol	108-01-0	0.1 ~ 1	

<4. First-aid measures >

Eye contact :

•Wash 15 minutes or more with plenty of clean water immediately. Wash completely to the reverse side of an eyelid.

· Receive the diagnosis of physician as soon as possible.

Skin contact :

- Wipe quickly clinging matter with clean cloth.
- Wash the affected area with plenty of running water using a mild soap or skin shampoo. Don't use solvents and thinner.
- · Arrange medical treatment by a physician on injured skin and painful parts.

Inhalation :

- Remove the victim inhale solvent vapor and gasses in abundance to fresh air and keep in warm and quiet. If breathing is weak, irregular or has stopped, open his airway, loose his collar and belt and administer artificial respiration. Arrange medical treatment by a physician as soon as possible.
- Remove the victim inhale vapor and gasses of organic solvents and more to fresh air and keep quiet. Then, arrange medical care.

Ingestion :

- If swallow in the wrong, keep the victim quiet and arrange medical inspection by physician, immediately.
- Prevent to swallow the vomiting.
- · Don't vomit things forcibly except dependence on the instruction of physician.
- <5. Fire-fighting measures >
 - Extinction medicine : There is no combustion in this product.
- <6. Accidental release measures >
 - · Wear proper protective equipment's (Gloves, protective mask, apron and goggles)
 - · Take up and place in closed container and keep in safety zone.
 - · Ensure treatment of the contaminated and waste in compliance with government requirements.
 - · Collects with the shovel, cloth slice, and etc. For large spills, dike for pollution further release.
 - Be careful not to be exhausted to the river etc. and be careful not to cause the influence on the environment.

MIZUTANI PAINT CO., LTD. 4-3-90 Nishimikuni, Yodogawa-ku, Osaka Japan TEL 81-6-6391-3151 FAX 81-6-6393-1101 3536-0000-B 3/4

MIZUKEI BOUJINTEX PROEPO PRIMER BASE

- <7. Handling and storage >
 - Handling :
 - · Use only in the well-ventilated areas. · Keep container tightly and closely.
 - Use adequate exhaust ventilation in closed area and ware proper protective equipment during using these materials.
 - Wear a protection tool appropriate which touches eyes, the skins, mucous membranes, and clothes.
 - Wash your the hand and face, etc. well after handling. Don't bring the pollution protection tool into the rest room.
 - •The person who has experienced an allergic condition in the past must not handle this product. Storage :
 - Protect from direct sunlight.
 - · Store in a cool dry, well-ventilated location.
 - When the product is kept, the temperature is not adjusted to 5°C or less or 40°C or more.
- <8. Exposure controls/protection >
 - Exposure density of hazardous, harmful element : Information is not possessed.
 - Equipment requirement: Special measures are unnecessary.
 - Protection tool :
 - · Eye protection ; Wear protective goggles.
 - · Skin protection ; Wear impervious clothing such as gloves, apron and body suits.
- Respiratory protection ; Wear the mask which prevents mist being inhaled when the spray working. <9. Physical and chemical properties >
- < 9. Physical and chemical prope
 - Appearance :
 - Form : Liquids
 Odor : Slightly amine odor
 - Specific temperatures/temperature ranges at which changes in physical sate occur :
 - Density ; 1.33 \sim 1.37 g/cm^3 $\,$ Solubility $\,$; It disperses to water.
- <10. Stability and reactivity >
 - Stability:
 - · There is no problem in stability in preservation under the room temperature.
 - Hazardous polymerization reaction:
 - The product unit is not polymerized. After BASE and HARDENER are mixed, if left to itself, the mixture gels.
 - Conditions to avoid:
 - Don't heat the product. Pressure rises abnormally in the airtight container, and there are an explosion and dread of the ignition.
 - Hazardous decomposition products;
 - · CO and a harmful gas such as NOx might be generated by combustion etc.
- <11. Toxicological information >
 - Acute toxicity : Information is not possessed.
 - Sensitization : Information is not possessed.
 - Carcinogenicity : Information is not possessed.
 - Mutating primeval : Information is not possessed.
 - Reproduction toxicity : Information is not possessed.
 - Mutagenicity : Information is not possessed.
- Others information : Modified aliphatic polyamine has the dread of skin obstacle by contact.

<12. Ecological information >

- · Note the handling of the leakage thing and waste because it might influence the environment.
- Deal so that neither the product nor the washing water may flow directly to ground, the river, and the drain ditch.
- Information is not possessed about decomposition, accumulation, and the fish toxicity of the product.

MIZUTANI PAINT CO., LTD. 4-3-90 Nishimikuni, Yodogawa-ku, Osaka Japan TEL 81-6-6391-3151 FAX 81-6-6393-1101 3536-0000-B 4/4

MIZUKEI BOUJINTEX PROEPO PRIMER BASE

<13. Disposal considerations >

- Waste paints and opened containers should be asked to dispose with licensed industrial waste treatment company.
- · Don't wash away the water used for cleaning of vessels and equipment into shower or water way.
- The wastes producing form process of water refining and of incineration should be disposed of in accordance with governmental laws and environmental control regulations or asked of dispose with licensed special company.

<14. Transport information >

General :

- · Transport and store according to general caution and instructions in before mentioned comment.
- Load the product for the fall and no damage after it is confirmed that there is no leakage in the container.
- · Do the collapse of cargo piles prevention surely.
- Land transportation : It doesn't correspond to regulations.

Maritime transportation : It doesn't correspond to regulations.

Air transportation : It doesn't correspond to regulations.

U.N. Number : It doesn't correspond to regulations.

- <15. Regulatory information >
 - It doesn't correspond to related regulations.

<16. Other information >

- The main quotation document :
- · Japan Paint Manufacturers Association edit " The SDS label preparation guidebook corresponding to GHS"
- · Japan Paint Manufacturers Association edit " The substance database for SDS"
- · Solvent pocket book

The information and recommendations in this publication are to the best of our knowledge, information and belief accurate at the date of publication. Nothing herein in to be construed as a warranty, express or implied.

In all cases it is the responsibility of the users to determine the applicability of such information or the suitability of any products for their own particular purpose.

MIZTERI MIZUTANI PAINT CO., LTD.

4-3-90 Nishimikuni, Yodogawa-ku, Osaka Japan TEL 81-6-6391-3151 FAX 81-6-6393-1101 3536-0011-B 1/4

MIZUKEI BOUJINTEX PROEPO PRIMER HARDENER

SAFETY DATA SHEET

<1. Product and company identification > Product Name MIZUKEI BOUJINTEX PROEPO PRIMER HARDENER Reference No. 3536-0011 Company MIZUTANI PAINT CO., LTD. 03-90, NISHIMIKUNI 4-CHOME YODOGAWA-KU, OSAKA, JAPAN Address Section concerned Quality Assurance Dep. 06-6394-2653 FAX No. 06-6391-3429 Phone No. Emergency contact Mizutani Paint Co., Ltd. Production Dep. Emergency phone No. 06-6391-3151 Product type Water soluble epoxy resin paint, under coat HARDENER Principal use Building materials use, others Feb.15, 2016 Date Dec.12, 2018 Revision day <2. Hazards identification > [GHS classification] Flammable liquids : Not classified Acute toxicity (oral) : Not classified Acute toxicity (skin) : Not classified Acute toxicity (inhalation: gas) : Not applicable Acute toxicity (inhalation: vapour) : Not classified Acute toxicity (inhalation: dust, mist) : Not classified Skin corrosion / irritation : Category 2 Serious eye damages / eye irritation : Category 2 Respiratory sensitization : Classification not possible Skin sensitization : Category 1 Germ cell mutagenicity : Not classified Carcinogenicity : Not classified Reproductive toxicity : Not classified Specific target organ toxicity single exposure : Not classified Specific target organ toxicity repeated exposure : Not classified Aspiration hazard : Not classified Aquatic toxicity (acute) : Category 2 Aquatic toxicity (chronic) : Category 2 Hazardous to the ozone layer : Classification not possible [GHS label elements including precautionary statements]



Signal word : WARNING [Hazard statement] • Causes skin irritation.

- Causes serious eve irritation.
- May causes an allergic skin reaction.
- Toxic to aquatic life.
- · Toxic to aquatic life with long lasting effects.



4-3-90 Nishimikuni, Yodogawa-ku, Osaka Japan TEL 81-6-6391-3151 FAX 81-6-6393-1101

3536-0011-B 2/4

MIZUKEI BOUJINTEX PROEPO PRIMER HARDENER

[Precautionary statements] [Prevention]

- · Keep container tightly closed.
- · Keep away from heat/sparks/open flames/hot surfaces. No smoking.
- · Use explosion-proof electrical/ventilating/lighting/ equipment.
- Do not eat, drink or smoke when using this product.
- · Wear protective gloves/protective clothing/eye protection/face protection.
- Use only outdoors or in well-ventilated area.
- · Wash hands thoroughly after handling.
- Avoid release to the environment.

[Response]

- In case of fire: Don't use water. Use the specific extinguishing media (Powder, CO 2, Foams).
- If in eyes: Rinse cautiously with water for 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a physician.
- · If swallowed: Rinse mouth with water. Do not induce vomiting. Immediately call a physician.
- If on skin : Remove all contaminated clothing. Wash with plenty of soap and water.
- · Arrange medical treatment by a physician on injured skin and painful parts.
- If inhaled: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
- · If exposed or concerned, or if you feel unwell: Get medical advice/attention.
- · At the leakage: Collect spillage.

[Storage]

• Store in a dry place. Keep container tightly closed in the locked place.

[Disposal]

- Dispose of contents / container to waste in accordance with local / regional / national / international regulations (to be specified).
- <3. Composition/information on ingredients > Distinction of chemical or mixture: mixture

Hazardous, harmful element:

Chemistry substance name	CAS No.	Content(%)	Note
Diglycidylether of BPA	25068-38-6	20~30	

<4. First-aid measures >

Eye contact :

- Wash 15 minutes or more with plenty of clean water immediately. Wash completely to the reverse side of an eyelid.
- Receive the diagnosis of physician as soon as possible.
- Skin contact :
- · Wipe quickly clinging matter with clean cloth.
- Wash the affected area with plenty of running water using a mild soap or skin shampoo. Don't use solvents and thinner.
- · Arrange medical treatment by a physician on injured skin and painful parts.

Inhalation :

• Remove the victim inhale solvent vapor and gasses in abundance to fresh air and keep in warm and quiet. If breathing is weak, irregular or has stopped, open his airway, loose his collar and belt and administer artificial respiration. Arrange medical treatment by a physician as soon as possible.

• Remove the victim inhale vapor and gasses of organic solvents and more to fresh air and keep quiet. Then, arrange medical care.

Ingestion :

• If swallow in the wrong, keep the victim quiet and arrange medical inspection by physician, immediately.

MIZUTANI PAINT CO., LTD. 4-3-90 Nishimikuni, Yodogawa-ku, Osaka Japan TEL 81-6-6391-3151 FAX 81-6-6393-1101 3536-0011-B 3/4

MIZUKEI BOUJINTEX PROEPO PRIMER HARDENER

- Prevent to swallow the vomiting.
- · Don't vomit things forcibly except dependence on the instruction of physician.
- <5. Fire-fighting measures >
 - Extinction medicine : There is no combustion in this product.
- <6. Accidental release measures >
 - · Wear proper protective equipment's (Gloves, protective mask, apron and goggles)
 - · Take up and place in closed container and keep in safety zone.
 - · Ensure treatment of the contaminated and waste in compliance with government requirements.
 - · Collects with the shovel, cloth slice, and etc. For large spills, dike for pollution further release.
 - Be careful not to be exhausted to the river etc. and be careful not to cause the influence on the environment.
- <7. Handling and storage >
 - Handling :
 - · Use only in the well-ventilated areas. · Keep container tightly and closely.
 - Use adequate exhaust ventilation in closed area and ware proper protective equipment during using these materials.
 - Wear a protection tool appropriate which touches eyes, the skins, mucous membranes, and clothes.
 - Wash your the hand and face, etc. well after handling. Don't bring the pollution protection tool into the rest room.
 - •The person who has experienced an allergic condition in the past must not handle this product. Storage :
 - Protect from direct sunlight.
 - · Store in a cool dry, well-ventilated location.
 - When the product is kept, the temperature is not adjusted to 5 $^\circ \! \mathrm{C}$ or less or 40 $^\circ \! \mathrm{C}$ or more.

<8. Exposure controls/protection >

Exposure density of hazardous, harmful element : Information is not possessed.

Equipment requirement: Special measures are unnecessary.

Protection tool :

- · Eye protection ; Wear protective goggles.
- · Skin protection ; Wear impervious clothing such as gloves, apron and body suits.
- Respiratory protection ; Wear the mask which prevents mist being inhaled when the spray working.
- <9. Physical and chemical properties >

Appearance :

- · Form : Liquids
- Specific temperatures/temperature ranges at which changes in physical sate occur :

• Density ; 1.00 \sim 1.04 g/cm³ • Solubility ; It disperses to water.

<10. Stability and reactivity >

Stability:

· There is no problem in stability in preservation under the room temperature.

• It reacts with amines, amides, and acid, etc.

Hazardous polymerization reaction:

• The product unit is not polymerized. After BASE and HARDENER are mixed, if left to itself, the mixture gels.

Conditions to avoid:

• Don't heat the product. Pressure rises abnormally in the airtight container, and there are an explosion and dread of the ignition.

Hazardous decomposition products;

· CO and a harmful gas such as NOx might be generated by combustion etc.

MIZUTANI PAINT CO., LTD. 4-3-90 Nishimikuni, Yodogawa-ku, Osaka Japan TEL 81-6-6391-3151 FAX 81-6-6393-1101 3536-0011-B 4/4

MIZUKEI BOUJINTEX PROEPO PRIMER HARDENER

- <11. Toxicological information > Skin corrosion / irritation : Category 2 Serious eye damages / eye irritation : Category 2 Skin sensitization : Category 1
- <12. Ecological information > Aquatic toxicity (acute) : Category 2 Aquatic toxicity (chronic) : Category 2
 - · Note the handling of the leakage thing and waste because it might influence the environment.
 - Deal so that neither the product nor the washing water may flow directly to ground, the river, and the drain ditch.
 - Information is not possessed about decomposition, accumulation, and the fish toxicity of the product.

<13. Disposal considerations >

- Waste paints and opened containers should be asked to dispose with licensed industrial waste treatment company.
- Don't wash away the water used for cleaning of vessels and equipment into shower or water way.
- The wastes producing form process of water refining and of incineration should be disposed of in accordance with governmental laws and environmental control regulations or asked of dispose with licensed special company.

<14. Transport information >

General :

Transport and store according to general caution and instructions in before mentioned comment.
Load the product for the fall and no damage after it is confirmed that there is no leakage in the

container.

· Do the collapse of cargo piles prevention surely.

Land transportation:

• Transport this product in compliance with the Fire-fighting Law, Law of Industrial Safety & Hygiene and Poisonous & Deleterious Material Control Law, if any.

Maritime transportation:

· Maritime transportation should be in compliance with [SENPAKU-ANZEN-HOU]

Air transportation:

· Air transportation should be in compliance with the Aviation Act.

U.N. Number : It doesn't correspond to regulations.

<15. Regulatory information >

It doesn't correspond to related regulations.

<16. Other information >

The main quotation document :

- · Japan Paint Manufacturers Association edit " The SDS label preparation guidebook corresponding to GHS"
- · Japan Paint Manufacturers Association edit " The substance database for SDS"
- · Solvent pocket book

The information and recommendations in this publication are to the best of our knowledge, information and belief accurate at the date of publication. Nothing herein in to be construed as a warranty, express or implied.

In all cases it is the responsibility of the users to determine the applicability of such information or the suitability of any products for their own particular purpose.